

DX-D 40

DIGITAL AED DETECTOR

The DX-D 40 Digital Detector with Automatic Exposure Detection (AED) offers a fast and effective way for radiography facilities to benefit from high quality digital imaging using virtually any X-ray equipment.

- The easiest and most versatile way to go Direct Digital
- Automatic Exposure Detection (AED) allows seamless use with virtually all X-ray systems, maximizing the use of the existing X-ray equipment
- Improved workflow and exam speed
- Cassette-sized detector gives maximum convenience and portability
- Excellent connectivity with DICOM compatible software and imagers
- MUSICA processing for excellent contrast detail and exam-independent, consistent image quality
- Choice of Cesium Iodide (CsI) or Gadolinium Oxy-Sulphide (GOS) detector conversion screens

The easiest way to go “instant DR”

For both conventional and mobile digital X-ray systems, the DX-D 40 Digital Detector offers general radiography facilities all the advantages of Direct Digital, while maximizing the use of their existing equipment. The Automatic Exposure Detection (AED) means no electrical connection to the X-ray system is required, for seamless use with virtually all X-ray systems.

At 43 x 35 cm in size, the detector fits into any standard bucky tray and can be easily removed to provide versatility for all exams. Wireless technology enhances operator comfort, and improves exam flexibility and convenience, even in challenging imaging situations.





Faster and more efficient workflow

The DX-D 40 is an integral part of an Agfa Instant DR solution, which includes the NX image acquisition software with MUSICA processing and detector. These cassette-less and filmless solutions provide a range of workflow benefits that improve productivity and speed up exam time. Retakes can be made immediately without changing cassette, and the number of images is no longer limited by the availability of cassettes. To complete the workflow, images can be sent immediately to a PACS or imager in DICOM format.

MUSICA and DR image quality: improved diagnostic confidence

The DX-D 40 is compatible with our 'gold standard' MUSICA image processing, which has been specially adapted and tuned to further enhance the excellent DR image quality. Exam-independent, it delivers consistent image quality and high contrast detail.

Combining MUSICA with the high quality of the DX-D 40, in terms of both sensitivity and sharpness, provides improved diagnostic confidence and efficiency.

Services & Support

Agfa offers service agreement solutions tailored to the customer's situation. Available in Basic, Comfort and Advanced levels, they make your lifecycle costs predictable.

A worldwide team of some 1,000 service professionals can provide support at all phases of your project, and even help customize your examination tree or link RIS protocol codes, further improving your return on investment. This team goes well beyond maintenance support, offering value-added services such as super user training, staff training and software upgrades.

Extended warranty options are available for the DX-D 40.

Technical Specifications

DETECTOR

- **Detector type:** Amorphous Silicon with TFT
- **Conversion screen:** Csl and GOS
- **Effective image area:**
 - Csl: 355.0 x 426.7 mm
 - GOS: 356.7 x 428.0 mm
- **Effective pixel matrix:**
 - Csl: 2536 x 3048 pixels
 - GOS: 2548 x 3060 pixels
- **Active pixel area (H x V):** 358.4 x 430.1 mm
- **Active pixel matrix (H x V):** 2560 x 3072 pixels
- **Pixel Pitch:** 140 µm
- **Grayscale:** 14 bit
- **Spacial Resolution:** Min. 3.5 lp/mm
- **ISO 4090**
- **Outer dimensions:** 384 x 460 x 15 mm
- **Weight:**
 - Csl: 3.4 kg
 - GOS: 3.3 kg
- **Energy Range Standard:** 40 – 150 kVp
- **Wireless data transmission from detector to access point:** IEEE 802.11a/b/g/n (2.4 GHz/5 GHz)
- **Recommended cycle time:** 15 s

Environmental Requirements

Operation

- **Temperature:** +10 ~ +35° C
- **Humidity:** 30 ~ 85% Rh (non condensing)
- **Atmospheric pressure:** 70 ~ 106 kPa
- **Shock:** 20 G
- **Vibration:** 2 G
- **Drop limits:** Max. 700 mm

Storage and transportation

- **Temperature:** -15 ~ +55° C
- **Humidity:** 10 ~ 90% Rh (non condensing)
- **Atmospheric pressure:** 50 ~ 106 kPa
- **Shock:** 30 G
- **Vibration:** 5 G
- **Drop limits:** Max. 700 mm

BATTERY SPECIFICATIONS

- **Type:** Lithium Ion Polymer Battery
- **Capacity:** 4000 mAh
- **Nominal Voltage:** 7.4 V
- **Charging time:** 2 Hours
- **Operation time:** 4 hours
- **Cycle life:** Approx. 500 cycles, Capacity ≥ 80% (100% = 4000 mAh)

SYSTEM CONTROL UNIT

Power supply

- **Input:** AC 100 to 240 V, 50/60 Hz, Max. 200 VA
- **Output:** DC +24 V 3.3 A, 80 W

Cabling ports

- **Gigabit Ethernet Ports – 3EA**
- **Power over Ethernet Ports – 2EA**
- **Wireless communications:** IEEE 802.11a/b/g/n (2.4 GHz/5 GHz)
- **Dimensions (W x H x D):** 300 x 235.8 x 58 mm, Antenna height – 105 mm
- **Weight:** 2.5 kg

Environmental Requirements

Operation

- **Temperature:** +10 ~ +35° C
- **Humidity:** 30 ~ 85% Rh (non condensing)
- **Atmospheric pressure:** 70 ~ 106 kPa

Storage and transportation

- **Temperature:** -15 ~ +55° C
- **Humidity:** 10 ~ 90% Rh (non condensing)
- **Atmospheric pressure:** 50 ~ 106 kPa
- **Altitude:** Maximum 2000 meters

DX-D 40

For more information on Agfa, please visit our website on www.agfa.com ■

Agfa and the Agfa rhombus are trademarks of Agfa-Gevaert NV, Belgium, or its affiliates. DX-D and MUSICA are trademarks of Agfa-Gevaert NV, Belgium, or its affiliates. All rights reserved. All information contained herein is intended for guidance purposes only, and characteristics of the products and services described in this publication can be changed at any time without notice. Products and services may not be available for your local area. Please contact your local sales representative for availability information. Agfa-Gevaert NV diligently strives to provide as accurate information as possible, but shall not be responsible for any typographical error.

© 2018 Agfa NV
All rights reserved
Published by Agfa NV
Septestraat 27 - 2640 Mortsel
Belgium

52T4J GB 00201803

AGFA 